



KIOSK FOR DISABLED USE

Active Series



PUBLIC CORPORATION



AMUSEMENT CENTER



SCHOOL



CINEMA



FAIR & ORGANIZATION



HOSPITAL



BANK



MALL

Unisign kiosk which is suitable for people with physical disabilities is a stylish and convenient multi-touch screen product that can be adjusted according to the height of the user.



Special Applications for More Efficient Areas

The height-adjustable kiosk provides great ease of use and efficiency, especially for disabled users, and adds an aesthetic atmosphere to the environment where it is positioned.

Customizable Product Design

You can support your corporate identity with solutions for you, thanks to color, logo and special accessory applications.

Touch Technology

PCAP touch technology uses a sensor grid of micro-fine wires integrated into the glass, completely covering the screen. Thanks to the glass coating, the screens are durable and the touch function remains intact even if there is any damage to the cover glass. It can be used with a latex glove and stylus pen.

Long Life Industrial Design

They are long-lasting industrial products with the ability to work 24/7.



Height adjustment
up to 230 mm



PANEL

KS121EA-DP

KS150EA-DP

KS170EA-DP

KS185EA-DP

KS215EA-DP

Panel Size	12.1"	15"	17"	18.5"	21.5"
Panel Type	60Hz ELED	60Hz ELED	60Hz ELED	60Hz ELED	60Hz ELED
Resolution	1024*768	1024*768	1280*1024	1920*1080	1920*1080
Brightness (Typ.)	350 cd/m²	350 cd/m²	350 cd/m²	350 cd/m²	350 cd/m²
Contrast	1300:1 (Typ.) (TM)	1300:1(Typ.) (TM)	1300:1 (Typ.) (TM)	1300:1 (Typ.) (TM)	1300:1 (Typ.) (TM)
Viewing Angle	170°	170°	170°	170°	170°
Touch Type	PCAP - 2 Point	PCAP - 2 Point	PCAP - 2 Point	PCAP - 2 Point	PCAP - 2 Point
Active Display Area (mm)	243.36*184.32	304.2*228.3	342*274	410*231	476.64*268.11

PANEL CONNECTIVITY

Video Input	HDMI, VGA DVI	HDMI, VGA DVI	HDMI, VGA DVI	HDMI, VGA DVI	HDMI, VGA DVI
Video Output	N/A	N/A	N/A	N/A	N/A
Audio Input / Output	Stereo mini jack	Stereo mini jack	Stereo mini jack	Stereo mini jack	Stereo mini jack
USB	N/A	N/A	N/A	N/A	N/A
Internal Control	N/A	N/A	N/A	N/A	N/A

POWER

Power Type	Adapter	Adapter	Adapter	Adapter	Adapter
Power Requirement	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz
Power Consumption	22 W	27 W	27 W	42 W	49 W
Standby Mode	< 0.5 W	< 0.5 W	< 0.5 W	< 0.5 W	< 0.5 W

DIMENSIONS

Product Size (mm)	500 * 1300 * 350	550 * 1300 * 350	600 * 1450 * 400	650 * 1450 * 400	740 * 1485 * 425
Package Size (mm)	550 * 1400 * 400	600 * 1400 * 400	650 * 1550 * 450	730 * 1550 * 450	800 * 1600 * 475
Product Weight (kg)	32	36	40	40	42
Package Weight (kg)	40	44	48	48	50

OPERATION

Working Life	7/24 - 50.000 hours	7/24 - 50.000 hours	7/24 - 50.000 hours	7/24 - 50.000 hours	7/24 - 50.000 hours
Working Conditions	Working Temp.:0~ 50 °C ; Storage Temp.: -20~60 °C	Working Temp.:0~ 50 °C ; Storage Temp.: -20~60 °C	Working Temp.:0~ 50 °C ; Storage Temp.: -20~60 °C	Working Temp.:0~ 50 °C ; Storage Temp.: -20~60 °C	Working Temp.:0~ 50 °C ; Storage Temp.: -20~60 °C
Humidity	10 ~ 80%	10 ~ 80%	10 ~ 80%	10 ~ 80%	10 ~ 80%

CERTIFICATION AND COMPATIBILITY

Safety	EN60950-1	EN60950-1	EN60950-1	EN60950-1	EN60950-1
EMC	Class A	Class A	Class A	Class A	Class A
Environment	ENERGY STAR 6.0 (USA)	ENERGY STAR 6.0 (USA)	ENERGY STAR 6.0 (USA)	ENERGY STAR 6.0 (USA)	ENERGY STAR 6.0 (USA)

OPTIONAL ACCESSORIES

Barcode, NFC, RFID, Beacon, Bluetooth, Camera, Pin, Industrial keyboard, Receipt printer, Audio system, Glass protector, Mirror protector, Glass logo, Colorful glass

OTHER

Included in pack	Easy installation guide, Warranty document, Power cable, (Other accessories externally)
------------------	--

unisign / DISPLAY
TECHNOLOGY



unisigns



unisigns



unisigns



unisign

www.unisign.com.tr
hello@unisign.com.tr



**KIOSK
for
DISABLED USE**