Samsun Self Order

Single & Dual-Side Self Order Kiosk

Two-sided choice. Flexible installation.

Available in 27-inch and 32-inch portrait displays, Samsun comes in single-sided KSSA and dual-sided KSSB configurations. Mount it to a wall or pipe without a floor stand, use it on a desktop, or choose the optional floor stand.



KSSA | SINGLE-SIDE



KSSB | DUAL-SIDE PROFILE

27 / 32	1 / 2	300 / 400	24/7	BRAND
inch	sided	cd/m²	50,000 h	ready

KSSA270EA / KSSA320MA: single-sided | KSSB270EA / KSSB320MA: dual-sided | Floor stand, logo and brand-color customization available.

FLEXIBLE SELF ORDER

One kiosk family. More ways to deploy.

Choose a one-sided or two-sided configuration, then match the mounting style to your space.

01 Single- or dual-side

KSSA serves one direction; KSSB presents ordering on both sides.

02 27-inch or 32-inch

Portrait Full HD touch displays, with brightness selected by model.

03 Integrated transaction tools

Thermal printer, NFC and payment-terminal options support checkout workflows.

04 Brand-ready finish

Optional logo and brand-color customization for a cohesive installation.

MOUNTING OPTIONS

Configure without the floor base, or select the optional stand.

WALL MOUNT

Stand-free wall installation

PIPE MOUNT

Stand-free pipe installation

DESKTOP

Place on a counter or desk

FLOOR STAND

Optional freestanding base

Printer and audio are optional accessories. Payment terminal availability depends on project configuration.

SPECIFICATIONS / 01

Display & platform specifications

Side-by-side values for all four supplied model codes. Dual-side models use two displays.

DISPLAY

SPECIFICATION	KSSA 27"	KSSA 32"	KSSB 27"	KSSB 32"
Model code	KSSA270EA	KSSA320MA	KSSB270EA	KSSB320MA
Screen size	27"	32"	27"	32"
Resolution	1080 × 1920	1080 × 1920	1080 × 1920	1080 × 1920
Brightness	300 cd/m²	400 cd/m²	300 cd/m²	400 cd/m²
Contrast	1000:1	1200:1	1000:1	1200:1
Viewing angle	178° × 178°	178° × 178°	178° × 178°	178° × 178°
Response	14 ms	8 ms	14 ms	8 ms
Active area	597.89 × 336.31	698.40 × 392.85	597.89 × 336.31	698.40 × 392.85
Touch / glass	10-point PCAP / 6H	10-point PCAP / 6H	10-point PCAP / 6H	10-point PCAP / 6H

OPTIONAL PLAYER & POWER

SPECIFICATION	KSSA 27"	KSSA 32"	KSSB 27"	KSSB 32"
CPU / RAM	Quad Core / 4 GB	Quad Core / 4 GB	Quad Core / 4 GB	Quad Core / 4 GB
Storage / OS	32 GB / Android 11	32 GB / Android 11	32 GB / Android 11	32 GB / Android 11
I/O	HDMI, USB, Ethernet, Wi-Fi	HDMI, USB, Ethernet, Wi-Fi	HDMI, USB, Ethernet, Wi-Fi	HDMI, USB, Ethernet, Wi-Fi
Average power	22 W	47 W	2 × 22 W	2 × 47 W
Standby	< 0.5 W	< 0.5 W	< 0.5 W	< 0.5 W
Power input	AC 100–240 V, 50/60 Hz	AC 100–240 V, 50/60 Hz	AC 100–240 V, 50/60 Hz	AC 100–240 V, 50/60 Hz
Touch technology	Projected capacitive	Projected capacitive	Projected capacitive	Projected capacitive

* Optional integrated player specifications. Operating life: 24/7, 50,000 hours. Operating temperature: 0–50°C; storage: −20–60°C; humidity: 10–80%.

SPECIFICATIONS / 02

Dimensions, accessories & setup

Mechanical dimensions are in millimetres. The floor stand is an optional configuration.

MECHANICAL	KSSA 27"	KSSA 32"	KSSB 27"	KSSB 32"
Unit size (mm)	1089 × 485 × 150	1200 × 550 × 150	1089 × 485 × 190	1200 × 550 × 190
Package (mm)	1160 × 520 × 320	1270 × 620 × 320	1160 × 520 × 475	1270 × 620 × 475
Product weight	40 kg	45 kg	65 kg	75 kg
Package weight	45 kg	50 kg	70 kg	80 kg
Stand size (mm)	698 × 260 × 105	587 × 300 × 105	698 × 260 × 105	587 × 300 × 105
Stand package (mm)	780 × 350 × 470	670 × 210 × 470	780 × 350 × 470	670 × 210 × 470
Stand weight	22 kg	25 kg	22 kg	25 kg

AUDIO	8 Ω, 5 W × 2 (optional)
THERMAL PRINTER	80 mm (optional)
2D BARCODE	640 × 480p, 30 scans/sec (optional)
IN THE BOX	Installation guide, warranty document, power cable

Wall mount / pipe mount (without floor stand) | Desktop use | Optional floor stand | Logo and brand-color customization

* Stand measurements and weights are shared by screen size in the supplied specification sheet.